

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

XP-002282333

AN - 1995-110113 [35]

AP - JP19930224903 19930723; [Previous Publ. JP7032531]

CPY - KUWA-I

DC - A28 A92 P73

FS - CPI;GMPI

IC - B32B7/02 ; B32B9/00 ; B32B27/00 ; B32B27/06 ; C08J7/00 ; C08J7/04

MC - A06-A00E A12-P01B

PA - (KUWA-I) KUWAHARA Y

PN - JP3465311B2 B2 20031110 DW200377 B32B9/00 005pp

- JP7032531 A 19950203 DW199515 B32B9/00 005pp

PR - JP19930224903 19930723

XA - C1995-050211

XIC - B32B-007/02 ; B32B-009/00 ; B32B-027/00 ; B32B-027/06 ; C08J-007/00 ;
C08J-007/04

XP - N1995-086823

AB - J07032531 The plastic material consists of plastic material pref long moulding, 0.005-0.05 mum thick layer of the polymer with 2.0-2.3 of refraction index and 0.03-0.2mum thick of the top layer of silicon oxide with 1.4-1.6 of refraction index. The first layer is prepared by polymerising silicon cpd comprising 15% or more of Si, 20% or more of C and the rest of oxygen under the pressure from 3 multiplied by 10-3 to 3 multiplied by 10-2torr by plasma CVD method. The second layer contains 60% or more of silicon oxide with general formula SiO_x ($x=1.5-2.0$). Also claimed is the preparation.

- USE - For wrapping materials such as films, cups, bottles.
- ADVANTAGE - Very thin membrane reduces water vapour permeation under 0.5 g/ m2 day, and is reclaimed.

- (Dwg.0/0)

IW - GAS INSULATE PLASTICS MATERIAL THIN TRANSPARENT MEMBRANE SILICON COMPOUND PLASTIC MATERIAL SILICA TOP LAYER SPECIFIED REFRACT INDEX
IKW - GAS INSULATE PLASTICS MATERIAL THIN TRANSPARENT MEMBRANE SILICON COMPOUND PLASTIC MATERIAL SILICA TOP LAYER SPECIFIED REFRACT INDEX

NC - 001

OPD - 1993-07-23

ORD - 1995-02-03

PAW - (KUWA-I) KUWAHARA Y

TI - Gas insulating plastics material with thin transparent membrane of silicon cpd - has plastic material and silica top layer of specified refraction index

A01 - [001] 017 ; S9999 S1581 ; P0884 P0839 H0293 F41 D01 D11 D10 D19 D18 D31 D50 D63 D90 E21 E00 ; S9999 S1434 ; S9999 S1285-R ;

- [002] 017 ; ND01 ; Q9999 Q8560 Q8366 ; Q9999 Q8435 Q8399 Q8366 ; Q9999 Q8399-R Q8366 ; Q9999 Q8366-R ; N9999 N7158 N7034 N7023 ; K9698 K9676 ; N9999 N6906 ; ND07 ;

- [003] 017 ; B9999 B5163 B5152 B4740 ; B9999 B5243-R B4740 ; N9999 N7090 N7034 N7023 ; B9999 B5447 B5414 B5403 B5276 ;

A02 - [001] 017 ; G2346 G2335 D00 D09 O- 6A ; G2302 G2299 G2266 D01 Si 4A D11 D10 D50 D86 F86 F81 ; R00326 G0044 G0033 G0022 D01 D02 D12 D10 D51 D53 D58 D82 ; P1445-R F81 Si 4A ; L9999 L2619 L2506 ; K9665 ; L9999 L2528 L2506 ; H0033 H0011 ; P0033 ; P1423 Si 4A ; H0260 ; S9999 S1285-R ; L9999 L2766 ; P1150 ;

- [002] 017 ; ND01 ; Q9999 Q8560 Q8366 ; Q9999 Q8435 Q8399 Q8366 ;
Q9999 Q8399-R Q8366 ; Q9999 Q8366-R ; N9999 N7158 N7034 N7023 ;
K9698 K9676 ; N9999 N6906 ; ND07 ;
- [003] 017 ; B9999 B5243-R B4740 ; B9999 B4444 B4240 ; Q9999 Q8060 ;
B9999 B4875 B4853 B4740 ; K9610 K9483 ; N9999 N7090 N7034 N7023 ;
N9999 N7136 N7034 N7023 ; B9999 B5436 B5414 B5403 B5276 ; B9999
B4397 B4240 ; K9847-R K9790 ;